

Memo



To: Advisory Board of Directors

From: Stacey Yankee, District Administrator
 Ingrid S. Penney, Administrative Services Manager
 James Perry, Park Services Manager

Date: February 20, 2025

Subject: Capital Equipment Purchase Order Authorization
 Fund 337L for FY2024-25

Background:

The 2022 GO Bond, Series 2023 CIP Program includes a natural turf soccer field for the La Sierra Community Center. A new specialized reel mower will be needed for ongoing turf maintenance.

Discussion:

CRPD Staff researched the type of mower needed. The Toro Reelmaster 5610-D 4WD and components meet the performance requirements for maintaining the new turf. They are available on the CMAS with a lead time of one-year minimum from order to delivery. (Tear sheet and Quote for the mower are attached to this report.) Total cost of the mower and components: \$108,445.90.

Because the mower is needed to support the ongoing maintenance of the new turf, staff investigated using the 2022 GO Bond proceeds to fund its acquisition. Capital equipment is an eligible purchase category within the general obligation bond funds and interest earnings restrictions.

There will be other costs associated with the mower, annual maintenance costs which will be allocated through the General Fund 337A and storage.

RECOMMENDATION: Staff recommends authorization to order the Mower and components, as presented; to fund the purchase through interest earnings from the 2022 GO Bond, Series 2023, CIP Program 337L. If deemed necessary, staff requests authorization to pursue an AAR through the County to order the equipment.

TORO

Reelmaster® 5410/5510/5610

FAIRWAY MOWERS

FEATURES

- **Powerful Tier 4 Compliant Engines** – Featuring Yanmar® 3-cylinder, liquid-cooled, diesel engines.
- **Smart Power™** – Automatically adjusts the mower's ground speed for the terrain and cutting conditions to maintain desired reel speed, taking the guesswork out of a consistent cut.
- **Proven Reliability & Performance** – Time tested platform delivers exceptional durability, high performance and versatility.
- **Electronic Cruise Control** – Easily keep a consistent speed and reduce fatigue while mowing large areas.
- **Enhanced climbing and hillside stability** – CrossTrax® all-wheel drive system is based on the Toro patented Series/Parallel™ design. If one of the front tires begins to slip, power is transferred to the opposite rear tire for optimum traction.
- **Precise Monitoring & Control** – An onboard InfoCenter allows viewing and changing of settings. It also provides essential information about service intervals, diagnostics and faults.
- **Unparalleled Operator Comfort** – with a tilt steering wheel, easy-access steps, a deluxe suspension seat, and a well thought-out design that moved the radiator to the rear of the engine compartment to move heat rejection and noise away from operator, these fairway mowers are designed for comfortable, all-day operation.
- **Outstanding Quality of Cut** – Dual Precision Adjustment (DPA) cutting units, featuring Toro's EdgeSeries™ reels, combine to deliver a consistent, high quality cut and superior after cut appearance, while reducing maintenance with improved reel edge retention.

Leading by reputation.

Performance, productivity and quality are just words if a piece of equipment has not earned them through actual customer usage. After more than 10 years of satisfying customers, the Reelmaster 5410, 5510 and 5610 have earned a reputation for delivering exceptional performance, maximum productivity and high quality. And we haven't stood still over the years. Toro continues to spend time listening closely to our customers to better understand their evolving requirements. Based on customer input, Toro engineers continually work to refine and improve each fairway mower to meet those needs. Everything from operator comfort and efficiency, to tractor performance, to cutting unit after-cut-appearance

improvements, and even ease of maintenance is reviewed in our relentless effort to maximize productivity and efficiency.

**EdgeSeries™ Reels****SMART POWER™****Call your Toro distributor at 800-803-8676**

REELMASTER 5410-D TIER 4 DIESEL, MODEL 03952*	
ENGINE	Yanmar® 3-cylinder, liquid cooled, diesel engine. 36.8 hp (27.5 kW), 74.4 ft. lbs. (105 Nm) torque, 1.64 liter displacement.
LUBRICATION	Pressurized lubrication system with 5.0 quart (4.7 liter) capacity.
FUEL FILTER	Replaceable spin-on fuel filter/water separator.
AIR CLEANER	Heavy-duty three-stage, radial seal air cleaner with restriction indicator.
COOLING	Plate and bar radiator/oil cooler combination, 6.3 fins per inch, 10 quart (9.5 liter) capacity.
FUEL TANK CAPACITY	14 gallon (53 liter) capacity.
HYDRAULIC OIL CAPACITY	15 gallon (56.8 liter) capacity.
TRACTION DRIVE	Front drive wheels powered in a parallel circuit by an electronically controlled hydrostatic pump with individual wheel motors. All-wheel drive optional with CrossTrax® All-Wheel Drive system, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.
GROUND SPEED	0-10 mph (0-16 km/hr) forward transport; 0-8 mph (0-12.8 km/hr) mow; 0-5 mph (0-8 km/hr) reverse transport; 0-4 mph (0-6.4 km/hr) reverse mow.
TIRES	Front traction tires: 26.5 x 14-12 turf tires Rear steer tires: 20 x 12-10
MAIN FRAME	High strength steel frame with welded construction.
BRAKES	Dynamic braking through hydrostatic traction drive. Parking brake is activated when engine is turned off, when operator leaves seat, or by rocker switch.
STEERING	Rear wheel, power steering with an independent hydraulic pump and circuit.
GAUGES	InfoCenter™ onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics, indicates fuel level, coolant temp., low oil pressure, alternator, engine hours, engine rpm, voltage, reel speed, backlap speed, glow indicator (diesel), lift/lower indicator.
CONTROLS	Single foot-operated traction pedal. Hand-operated key ignition switch, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch, and headlight switch all positioned on right hand pivoting control console.
ELECTRICAL & INTERLOCKS	Heavy-duty 12-volt battery, 570 CCA, 55 amp alternator. Electronic control unit is a microprocessor based, solid state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat, and cutting unit engage/disengage safety interlock switches.
REEL DRIVE	Reel drive circuit is split independently for front and rear cutting units. Hydraulic functions controlled by an integrated hydraulic control block. Reel speeds are electronically adjustable in nine incremental settings. Desired clip rate remains consistent as max mow speed is adjusted. Standard on-board backlapping.
CUTTING UNIT LIFT/LOWER	Front and rear cutting unit lift/lower is sequenced for uniform starting and ending points.
SEAT	Deluxe high back suspension seat with fore, aft, height and weight adjustment.
ROPS	Standard with seat belt
HEIGHT	63" (160 cm) seat top, 85" (217.2 cm) top of ROPS.
LENGTH (2WD)	111" (281.9 cm)
WHEEL BASE	60" (152.4 cm)
OPERATIONAL WIDTH	113.5" (288.3 cm)
TRANSPORT WIDTH	92" (233.7 cm)
WEIGHT	2,943 lbs. (1,335 kg) (2WD), 3,053 lbs. (1,385 kg) (4WD)
CERTIFICATION	Complies with ANSI B71.4 and CE requirements. Certain machine configurations require rear weight kits for standards compliance, see Operator's Manual for details.
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Reelmaster 5410-D Accessories

8 AND 11-BLADE CUTTING UNITS, MODELS 03621, 03623 AND 03624	
TYPE	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.
SIZE	22" (56 cm) wide, 5" (12.7 cm) diameter, 8 & 11 blade cutting units.
WIDTH OF CUT	100" (254 cm)
HOC RANGE	8-Blade: 0.5" - 1.5" (13-38 mm), 11-Blade: 0.25" - 0.75" (6-19 mm)
REEL SPEED	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200-2,000 rpm with a backlap speed of 200 rpm.
BEDKNIFE ADJUSTMENT	Dual Precision Adjustment (DPA), bedknife to reel.
ROLLERS	3" (7.6 cm) diameter, deep groove plastic Wiehle front roller. 2.5" (6.4 cm) diameter shortened steel rear roller. Other roller configurations optional.

UNIVERSAL GROOMER, MODEL 03763	
TYPE	Forward, Reverse & Neutral. Rotating blades with optional Broomer™ brush strips that are woven within the blade helix for full width turf contact.
GROOMING WIDTH	20.5" (52.1 cm)
GROOMING RANGE	0-0.25" (0-6.4 mm) below height of cut when engaged, 0.5" (0-12.7 mm) above Groomer height of cut when disengaged.
BLADES	2.5" (6.4 cm) diameter, 0.042" (1 mm) thick heat treated spring steel blades with 0.5" (12.7 mm) spacing.

POWERED REAR ROLLER BRUSH, MODEL 03406	
TYPE	Rotating, helically woven, stiff bristled brush. Spring loaded belt drive.
CONTACT POINTS	Tightly woven 11-point contact.
SPIN RATE	Rapid 2000 rpm spin rate.

CUTTING UNITS	
03621	5" (12.7 cm) 8-blade DPA RR cutting unit
03623	5" (12.7 cm) 11-blade DPA FSR cutting unit
03624	5" (12.7 cm) 11-blade DPA RR cutting unit
03618	5" (12.7 cm) verticutter cutting unit

TRACTION UNIT ACCESSORIES	
03645	CrossTrax® All-Wheel Drive Kit
03667	Air-ride Seat Suspension
03614	Golf Ball Guard

TRACTION UNIT SUNSHADE	
30669	Universal Sunshade - White
30671	Universal Sunshade - Red
03248	Switch Panel
03247	Operator Cooling Fan
140-1554	Worklights
138-2699	Beacon
138-2994	Wire Harness

5" (12.7 cm) CUTTING UNIT ACCESSORIES	
03763	Universal Groomer
03772	22" (56 cm) Groomer Cartridge
03767	Grooming Brush Cartridge
03417	Universal Only Weight Kit
03658	Powered rear roller brush for groomers
03413	Weight for cutting units with attachments
03406	Powered rear roller brush only
03411	End Weight Kit
03415	Flex Grass Basket
131-6845	Flex Groomer Rod Kit

BEDKNIFE OPTIONS	
137-6094	EdgeMax™
108-9096	Standard
137-6093	EdgeMax Low Cut
110-4084	Low Cut
119-4280	EdgeMax Extended Low Cut
120-1640	Extended Low Cut
110-4074	Heavy Duty

SCRAPER OPTIONS	
107-3280	Rear Roller Scraper
107-2993-03	Wiehle Roller Scraper
110-1735	Comb Scraper Kit

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Reelmaster® 5510 / 5510-D Specifications

	REELMASTER 5510, MODEL 03964*	REELMASTER 5510-D, TIER 4 DIESEL, MODEL 03954*
ENGINE	Kubota® 4-cylinder, liquid cooled, diesel engine. 35.5 hp (26.5 kW) @ 3000 rpm.	Yanmar® 3-cylinder, liquid cooled, diesel engine. 36.8 hp (27.5 kW), 74.4 ft. lbs. (105 Nm) torque, 1.64 liter displacement.
LUBRICATION	Pressurized lubrication system with 5.0 quart (4.7 liter) capacity.	
FUEL FILTER	Replaceable spin-on fuel filter/water separator.	
AIR CLEANER	Heavy-duty three-stage, radial seal air cleaner with restriction indicator.	
COOLING	Rear mounted radiator with industrial tube and fin construction, 6.5 fins per inch, 7.0 quart (6.6 liter) capacity.	Plate and bar radiator/oil cooler combination, 6.3 fins per inch, 10 quart (9.5 liter) capacity.
FUEL TANK CAPACITY	13.5 gallon (51.1 liter) capacity. Biodiesel-Ready for use up to B-20 (20% biodiesel and 80% petroleum blend).	14 gallon (53 liter) capacity.
HYDRAULIC OIL CAPACITY	9.0 gallon (34.1 liter) capacity.	15 gallon (56.8 liter) capacity.
TRACTION DRIVE	Front drive wheels powered in a parallel circuit by an electronically controlled hydrostatic pump with individual wheel motors. All-wheel drive optional with CrossTrax® All-Wheel Drive system, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.	
GROUND SPEED	0-10 mph (0-16 km/hr) forward transport; 0-8 mph (0-12.8 km/hr) mow; 0-5 mph (0-8 km/hr) reverse transport; 0-4 mph (0-6.4 km/hr) reverse mow.	
TIRES	Front traction tires: 26.5 x 14-12 turf tires Rear steer tires: 20 x 12-10	
MAIN FRAME	High strength steel frame with welded construction.	
BRAKES	Dynamic braking through hydrostatic traction drive. Parking brake is activated when engine is turned off, when operator leaves seat, or by rocker switch.	
STEERING	Rear wheel, power steering with an independent hydraulic pump and circuit.	
GAUGES	InfoCenter™ onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics, indicates fuel level, coolant temp., low oil pressure, alternator, engine hours, engine rpm, voltage, reel speed, backlap speed, glow indicator (diesel), lift/lower indicator.	
CONTROLS	Single foot-operated traction pedal. Hand-operated key ignition switch, mechanical throttle, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch, and LED headlight switch all positioned on right hand pivoting control console.	Single foot-operated traction pedal. Hand-operated key ignition switch, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch, and LED headlight switch all positioned on right hand pivoting control console.
ELECTRICAL & INTERLOCKS	Heavy-duty 12-volt battery, 570 CCA, 40 amp alternator. Electronic control unit is a microprocessor based, solid state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat, and cutting unit engage/disengage safety interlock switches.	Heavy-duty 12-volt battery, 570 CCA, 55 amp alternator. Electronic control unit is a microprocessor based, solid state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat, and cutting unit engage/disengage safety interlock switches.
REEL DRIVE	Reel drive circuit is split independently for front and rear cutting units. Hydraulic functions controlled by an integrated hydraulic control block. Reel speeds are electronically adjustable in nine incremental settings. Desired clip rate remains consistent as max mow speed is adjusted. Standard on-board backlapping.	
CUTTING UNIT LIFT/LOWER	Front and rear cutting unit lift/lower is sequenced for uniform starting and ending points.	
SEAT	Deluxe high back suspension seat with fore, aft, height and weight adjustment.	
ROPS	Standard with seat belt	
HEIGHT	63" (160 cm) seat top, 85.5" (217.2 cm) top of ROPS.	
LENGTH (2WD)	111" (281.9 cm)	
WHEEL BASE	60" (152.4 cm)	
OPERATIONAL WIDTH	116" (288.3 cm)	
TRANSPORT WIDTH	92" (233.7 cm)	
WEIGHT	3,083 lbs (1,399 kg) (2WD), 3,193 lbs (1,449 kg) (4WD)	3,131 lbs. (1,420 kg) (2WD), 3,241 lbs. (1,470 kg) (4WD)
CERTIFICATION	Complies with ANSI B71.4 and CE requirements. Certain machine configurations require rear weight kits for standards compliance, see Operator's Manual for details.	
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Reelmaster® 5510 / 5510-D Accessories

8 AND 11-BLADE CUTTING UNITS, MODELS 03638, 03639, 03641, AND 03643	
TYPE	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.
SIZE	22" (56 cm) wide, 7" (17.8 cm) diameter, 8 and 11 blade cutting units.
WIDTH OF CUT	100" (254 cm)
HOC RANGE	8-Blade: 0.5"-2.0" (13-51 mm), 11-Blade: 0.25" - 0.75" (6-19 mm)
REEL SPEED	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200-1,650 rpm with a backlap speed of 200 rpm.
BEDKNIFE ADJUSTMENT	Dual Precision Adjustment (DPA), bedknife to reel.
ROLLERS	3" (7.6 cm) diameter, deep groove plastic Wiehle front roller. 3" (7.6 cm) diameter steel rear roller. Other roller configurations optional.

UNIVERSAL GROOMER, MODEL 03763	
TYPE	Forward, Reverse & Neutral. Rotating blades with optional Broomer™ brush strips that are woven within the blade helix for full width turf contact.
GROOMING WIDTH	20.5" (52.1 cm)
GROOMING RANGE	0-0.25" (0-6.4 mm) below height of cut when engaged, 0-0.25" (0-6.4 mm) above height of cut when disengaged.
BLADES	2.5" (6.4 cm) diameter, 0.042" (1 mm) thick heat treated spring steel blades with 0.5" (12.7 mm) spacing.

POWERED REAR ROLLER BRUSH, MODEL 03408	
TYPE	Rotating, helically woven, stiff bristled brush. Spring loaded belt drive.
CONTACT POINTS	Tightly woven 11 point contact.
SPIN RATE	Rapid 2000 rpm spin rate.

CUTTING UNITS	
03638	7" (17.8 cm) 8-blade DPA, RR cutting unit
03639	7" (17.8 cm) 8-blade DPA, FSR cutting unit
03641	7" (17.8 cm) 11-blade DPA, FSR cutting unit
03643	7" (17.8 cm) 11-blade DPA, RR cutting unit
03619	7" (17.8 cm) verticutter cutting unit

TRACTION UNIT ACCESSORIES	
03645	CrossTrax® All-Wheel Drive Kit
03667	Air-ride Seat Suspension
03614	Golf Ball Guard

TRACTION UNIT SUNSHADE	
30669	Universal Sunshade - White
30671	Universal Sunshade - Red
03248	Switch Panel
03247	Operator Cooling Fan
140-1554	Worklights
138-2699	Beacon
138-2994	Wire Harness

7" (17.8 cm) CUTTING UNIT ACCESSORIES	
03768	Universal Groomer
03772	22" (56 cm) Groomer Cartridge
03767	Grooming Brush Cartridge
03418	Universal Only Weight Kit
03659	Powered rear roller brush for groomers
03419	Universal w/RRB Weight Kit
03408	Powered rear roller brush only
03405	Weight for cutting units without attachments
03415	Flex Grass Basket
131-6845	Flex Groomer Rod Kit

BEDKNIFE OPTIONS	
137-6094	EdgeMax™
108-9096	Standard
137-6093	EdgeMax Low Cut
110-4084	Low Cut
119-4280	EdgeMax Extended Low Cut
120-1640	Extended Low Cut
110-4074	Heavy Duty

SCRAPER OPTIONS	
107-3280	Rear Roller Scraper
107-2993-03	Wiehle Roller Scraper
110-1735	Comb Scraper Kit

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Reelmaster® 5610 Specifications

	REELMASTER 5610 4WD, MODEL 03966*	REELMASTER 5610-D 4WD, MODEL 03956*
ENGINE	Kubota® 4-cylinder, liquid cooled, diesel engine. 44.2 hp (33 kW) @ 3000 rpm.	Yanmar® 3-cylinder, liquid cooled, turbo-diesel engine. 43.5 hp (32.4 kW), 74.4 ft. lbs. (105 Nm) torque, 1.64 liter displacement. Tier 4 Final Compliant.
LUBRICATION	Pressurized lubrication system with 5.0 quart (4.7 liter) capacity.	
FUEL FILTER	Replaceable spin-on fuel filter/water separator.	
AIR CLEANER	Heavy duty three-stage, radial seal air cleaner with restriction indicator.	
COOLING	Rear mounted radiator with industrial tube and fin construction, 6.3 fins per inch, 10.0 quart (9.5 liter) capacity.	
FUEL TANK CAPACITY	13.5 gallon (51.1 liter) capacity. Biodiesel-Ready for use up to B-20 (20% biodiesel and 80% petroleum blend).	
HYDRAULIC OIL CAPACITY	9.0 gallon (34.1 liter) capacity.	
TRACTION DRIVE	Electronically controlled hydrostatic pump with individual wheel motors. CrossTrax® All-Wheel Drive system standard, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.	
GROUND SPEED	0-10 mph (0-16 km/hr) forward transport; 0-8 mph (0-12.8 km/hr) mow; 0-5 mph (0-8 km/hr) reverse transport; 0-4 mph (0-6.4 km/hr) reverse mow.	
TIRES	Front traction tires: 26.5 x 14-12 turf tires; Rear steer tires: 20 x 12-10.	
MAIN FRAME	High strength steel frame with welded construction.	
BRAKES	Dynamic braking through hydrostatic traction drive. Parking brake is activated when engine is turned off, when operator leaves seat, or by rocker switch.	
STEERING	Rear wheel, power steering with an independent hydraulic pump and circuit.	
GAUGES	InfoCenter™ onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics, indicates fuel level, coolant temp., low oil pressure, alternator, engine hours, engine rpm, voltage, reel speed, backlap speed, glow indicator (diesel), lift/lower indicator.	
CONTROLS	Single foot-operated traction pedal. Hand-operated key ignition switch, mechanical throttle, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch, and LED headlight switch all positioned on right hand pivoting control console.	Single foot-operated traction pedal. Hand-operated key ignition switch, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch, and LED headlight switch all positioned on right hand pivoting control console.
ELECTRICAL & INTERLOCKS	Heavy duty 12-volt battery, 570 CCA, 40 amp alternator. Electronic control unit is a microprocessor based, solid state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat, and cutting unit engage/disengage safety interlock switches.	
REEL DRIVE	Reel drive circuit is split independently for front and rear cutting units. Hydraulic functions controlled by an integrated hydraulic control block. Reel speeds are electronically adjustable in nine incremental settings. Desired clip rate remains consistent as max mow speed is adjusted. Standard on-board backlapping.	
CUTTING UNIT LIFT/LOWER	Front and rear cutting unit lift/lower is sequenced for uniform starting and ending points.	
SEAT	Deluxe high back suspension seat with fore, aft, height and weight adjustment.	
ROPS	Standard with seat belt	
HEIGHT	63" (160 cm) seat top, 85.5" (217.2 cm) top of ROPS.	
LENGTH	111" (281.9 cm)	
WHEEL BASE	60" (152.4 cm)	
OPERATIONAL WIDTH	116" (288.3 cm)	
TRANSPORT WIDTH	92" (233.7 cm)	
WEIGHT	3,213 lbs (1,458 kg)	3,261 lbs (1,480 kg)
CERTIFICATION	Complies with ANSI B71.4 and CE requirements. Certain machine configurations require rear weight kits for standards compliance, see Operator's Manual for details.	
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Reelmaster® 5610 Accessories

8 AND 11-BLADE CUTTING UNITS, MODELS 03638, 03639, 03641, AND 03643	
TYPE	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.
SIZE	22" (56 cm) wide, 7" (17.8 cm) diameter, 8 and 11 blade cutting units.
WIDTH OF CUT	100" (254 cm)
HOC RANGE	8-Blade: 0.5"-2.0" (13-51 mm), 11-Blade: 0.25" - 0.75" (6-19 mm)
REEL SPEED	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200-1,650 rpm with a backlap speed of 200 rpm.
BEDKNIFE ADJUSTMENT	Dual Precision Adjustment (DPA), bedknife to reel.
ROLLERS	3" (7.6 cm) diameter, deep groove plastic Wiehle front roller. 3" (7.6 cm) diameter steel rear roller. Other roller configurations optional.

UNIVERSAL GROOMER, MODEL 03763	
TYPE	Forward, Reverse & Neutral. Rotating blades with optional Broomer™ brush strips that are woven within the blade helix for full width turf contact.
GROOMING WIDTH	20.5" (52.1 cm)
GROOMING RANGE	0-0.25" (0-6.4 mm) below height of cut when engaged, 0-0.25" (0-6.4 mm) above height of cut when disengaged.
BLADES	2.5" (6.4 cm) diameter, 0.042" (1 mm) thick heat treated spring steel blades with 0.5" (12.7 mm) spacing.

POWERED REAR ROLLER BRUSH, MODEL 03408	
TYPE	Rotating, helically woven, stiff bristled brush. Spring loaded belt drive.
CONTACT POINTS	Tightly woven 11 point contact.
SPIN RATE	Rapid 2000 rpm spin rate.

CUTTING UNITS	
03638	7" (17.8 cm) 8-blade DPA, RR cutting unit
03639	7" (17.8 cm) 8-blade DPA, FSR cutting unit
03641	7" (17.8 cm) 11-blade DPA, FSR cutting unit
03643	7" (17.8 cm) 11-blade DPA, RR cutting unit
03619	7" (17.8 cm) verticutter cutting unit

TRACTION UNIT ACCESSORIES	
03667	Air-ride Seat Suspension
03614	Golf Ball Guard

TRACTION UNIT SUNSHADE	
30669	Universal Sunshade - White
30671	Universal Sunshade - Red
03248	Switch Panel
03247	Operator Cooling Fan
140-1554	Worklights
138-2699	Beacon
138-2994	Wire Harness

7" (17.8 cm) CUTTING UNIT ACCESSORIES	
03768	Universal Groomer
03772	22" (56 cm) Groomer Cartridge
03767	Grooming Brush Cartridge
03418	Universal Only Weight Kit
03659	Powered rear roller brush for groomers
03419	Universal w/RRB Weight Kit
03408	Powered rear roller brush only
03405	Weight for cutting units without attachments
03415	Flex Grass Basket
131-6845	Flex Groomer Rod Kit

BEDKNIFE OPTIONS	
137-6094	EdgeMax™
108-9096	Standard
137-6093	EdgeMax Low Cut
110-4084	Low Cut
119-4280	EdgeMax Extended Low Cut
120-1640	Extended Low Cut
110-4074	Heavy Duty

SCRAPER OPTIONS	
107-3280	Rear Roller Scraper
107-2993-03	Wiehle Roller Scraper
110-1735	Comb Scraper Kit

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Northern California Division
 PO Box 748728
 Los Angeles, CA, 90074-8728
 Phone: 800-585-8001

QUOTE

Quote Nbr.: Q004005
Order Date: 8/29/2024
Valid Until:
Sales Person: Tim McCoy
Customer ID: 02641
Reference:
Payment Terms:
For: Perry, James

Notes: Sourcewell Contract Toro 031121-TTC

FOR:	SHIP TO:	BILL TO:
Carmichael Park & Rec 5750 Grant Avenue Carmichael CA 95608 United States of America	Carmichael Park & Rec 5750 Grant Avenue Carmichael CA 95608 United States of America	Carmichael Park & Rec 5750 Grant Avenue Carmichael CA 95608 United States of America

NO.	ITEM	QTY.	UOM	PRICE	AMOUNT
1	03956: REELMASTER 5610-D 4WD(T4F/STAGE V)	1.0000	EA	71,543.1600	71,543.16
2	03639: 7In 8 Blade FSR DPA C/U	5.0000	EA	3,796.2600	18,981.30
3	03408: Rear Roller Brush Kit7in CU Set of 5	1.0000	EA	3,859.4400	3,859.44
4	137-0842: HD BRUSH-REAR ROLLER, 22IN	5.0000	EA	102.6402	513.20
5	03667: Air-Ride Seat Suspension	1.0000	EA	706.6800	706.68
6	133-1308: COVER SEAT,HI-BACK	1.0000	EA	64.7322	64.73
7	30671: Universal Sunshade Red	1.0000	EA	822.1200	822.12
8	FSD1: Setup	1.0000	EA	2,079.0000	2,079.00
9	FSD2: Delivery	1.0000	EA	2,079.0000	2,079.00

Signature:

Quote Total: 100,648.63
Tax Total: 7,800.27
Total (USD): 108,448.90



QUOTE

Quote Nbr.:

Q004005

Standard Terms and Conditions:

Prices including all finance options are subject to change based on Turf Star Western's receipt of product and estimated shipments. Currently, product availability is a minimum of 6-18 months. Your Final Price will be determined at the time of shipment. Delivery is FOB point of origina unless otherwise stated.

Office Locations:

Northern California:

3928 N. Blattela Lane
Fresno, CA 93727

11373 Sunrise Gold Circle
Rancho Cordova, CA 95742

Southern California:

79-893 Country Club Drive
Bermuda Dunes, CA 92203

955 Beacon Street
Brea, CA 92821

2255 Meyers Avenue
Escondido, CA 92029

Pacific Northwest:

1750 Industrial Dr. NE
Salem, OR 97301

5869 South 194th
Kent, WA 98032

2824 East Garland
Spokane, WA 99207

(800) 585-8001



WARNING:

Cancer and Reproductive Harm - <http://www.P65Warnings.ca.gov>
For more information, please visit <https://www.ttcoCAProp65.com>

CALIFORNIA SPARK ARRESTER WARNING:

Operation of this equipment in the State of California may create sparks that can start fires around dry vegetation
A spark arrestor may be required.
The operator should contact local fire agencies for laws or regulations relating to fire prevention requirements